

Similar image

DATA SHEET  
LABEL PRINTER AND  
APPLICATOR

LEGI-AIR 4050 M



**Weber**<sup>®</sup>  
LABELING & CODING SOLUTIONS

# LEGI-AIR 4050 M

**Next generation label printer and applicator: an innovative control concept allows LEGI-AIR 4050 M to print and apply labels fully automatically in a single operation. The "M" in this case stands for "Master controller" as the central interface for data and process control. The consistent modular design and the use of print modules from leading manufacturers assure both the fulfilment of the widest variety of labeling requirements and easy integration into existing plant and equipment.**

## Practical

In this system the labeller itself undertakes the formatting of the user data, thus handling this aspect independently of the various printer manufacturers. This means that the best suited print module for the respective application can be selected with no need to adjust the customer's controls. The complete system is controlled via an interface – the connection is made over RS 232, 422, 485, Ethernet or Profibus.

## Versatile


LEGI-AIR 4050 M facilitates the use of a multiplicity of standard applicators and can also be converted for RFID labeling. Various

modes of operation, e.g. contactless air blast processes such as "Blow-On" and "Tamp-Blow" for high-speed labeling, emphasize the practical strengths of the system. Numerous individual solutions are also possible due to the fact that all labeling and installation positions can be achieved with the standard equipment.

## User-oriented

LEGI-AIR 4050 M offers additional useful features ideal for everyday applications. Functions such as a remote servicing option via internet or network and the integrated service interval display guarantee the daily flow of production. Events such as "end of label roll" can be pre-defined – when this occurs a message is sent via signal light, e-mail or by SMS to a mobile phone. Classic digital I/O signals are also available.

The multi-language 5.7" (optional 10.4") touch display for polling, editing and storing data makes a PC connection superfluous. The equipment also has a USB connection which can be used to add a separate keyboard for direct data entry or to connect a data carrier.



## Technical specifications:

### Printing technology

Thermal transfer or direct thermal

### Print resolution

- 8 dots/mm (203 dpi)
- 12 dots/mm (300 dpi)
- 24 dots/mm (600 dpi)

### Print speed

Up to 400 mm per second

### Tamp sizes (mm)

Tamp-Blow standard of 12.5 x 7 to 160 x 300 mm, label lengths must be limited in accordance with label quality, longer or smaller labels are possible using special tamps

### Label gap

Minimum 3 mm

### Label roll

300 mm diameter, up to 450 running meters, core 76 mm (3"), outside winding (optional inside winding)

### Data interfaces

RS232, RS422, RS485, Ethernet

Optional: Profibus

### Service intervals

According to interval display

### Positional accuracy of applied labels

Up to ± 0.8 mm on stopped product (dependent on distance of application, type of applicator and label type)

### Print applicator activation

HOST connection, reflex button, light barrier, inductive or capacitive sensor, SPS output microswitch

### Alarm equipment

Standard: error reporting on 5.7" touch-display, host status, e-mail, digital I/O optional: 3-colour alarm lamp

### Display controller

- Multi-language operator guidance
- 5.7" VGA touch display
- Service interval indicator
- Poling, editing and saving of label data
- USB connection for memory medium or keyboard

### Application speed

Up to 200 labels per minute, the application capacity is dependent on label size, text change and stroke

### Compressed air consumption

0.3 to 3 l per application cycle, dependent on label size, applicator type and setting

### Compressed air connection

6 bar, the compressed air must be clean, dry and oil-free

### Dimensions (L x H x W)

770 x 560 x 580 mm,  
Applies to system with 250 mm stroke

### Weight

From 75 kg (depending on model)

### Electrical connection

90 to 263V AC, 50/60 Hz, 5 amps

### Ambient conditions

Temperature: 10°C to 35°C, 15 to 85% relative humidity, non-condensing  
(see separate leaflet on print modules).

### Accreditation

CE-mark

## Choice of options:

- 90° rotating tamp
- Corner wrap application
- Two-sided labeling
- 1-sided pallet labeller with extra long stroke
- Fast two-sided carton labeling
- Linear applicator up to 1200 mm stroke
- Short stroke high-speed linear applicators
- Vacuum belt applicator
- RFID labeling
- Quick-Change
- Spring loaded tamp (Gimbal)
- 3-colour alarm lamp
- Protective housing for installation under particularly difficult ambient conditions
- 10.4" touch display
- Profibus connection
- GSM module
- ID scanner
- Verifier scanner
- RFID reader

All technical specifications are dependent on the print modules used (see separate leaflet on print modules).



Screenshot Mastercontroller

**European Headquarter**  
**Weber Marking Systems GmbH**  
Honnefer Straße 41  
D-53572 Unkel  
Phone: +49 2224 7708 0  
Fax: +49 2224 7708 20  
info@webermarking.de  
www.webermarking.de

**Weber Marking Systems Ltd**  
Macmerry Industrial Estate, Macmerry  
East Lothian, EH33, 1HD  
Phone: +44 1875 61 1111  
Fax: +44 1875 61 3310  
sales@weber.co.uk  
www.weber.co.uk

**World Headquarter**  
**Weber Marking Systems, Inc.**  
711 W. Algonquin Road  
Arlington Heights, IL 60005-4457  
Phone: +1.847.364.8500  
Fax: +1.847.364.8575  
info@webermarking.com  
www.webermarking.com



**Weber®**  
LABELING & CODING SOLUTIONS